



1、SPECIFICATIONS:

Current Rating : 3.0 A
 Contact Resistance : 20mΩ Max
 Insulation Resistance : 1000MΩ Min
 Withstand Voltage : 1000V AC/minute
 Operation Temperature : -40° C ~ +105° C

2、MATERIALS:

Contact Material : Copper Alloy
 Contact Plating : Gold/Tin Plated over Ni
 Insulator Material : PA6T BK (UL94V-0)
 Max Processing Temp : 230° C for 30 Seconds
 260° C for 5~10 Seconds

Ordering Informations

2422 XX X N XX M X XXX

- ①
- ②
- ③
- ④
- ⑤
- ⑥
- ⑦
- ⑧

STANDARD	
PA	6.00
PB	10.00
W	7.50
D	1.20
H	2.50

- ① 2422 Pin Header- 2.54 Dual Row Series (H2.5MM)
- ② XX NO. of Contacts Per row 02=2PIN 02=10P
- ③ X Insulator Material A=PBT C=PA6T D=PA9T F=LC²
- ④ N Posts W=With Post
- ⑤ XX Contact Plated G=Gold Flash G0=8μ" gold G1=10" Gold G5=10μ" Gold S=Tin Plated
- ⑥ M Mounting Type D=DIP R=Right Angle M=SMT Z=Recomment U=U Type
- ⑦ X Packing O=Pipe Bag T=tube A=Tray P=Mylar-Tube R=Reel-CAP M=Carrier-Reel
- ⑧ XXX Serial NO. 001 001~999

TOLERANCES UNLESS OTHERWISE SPECIFIED

X ~~~~ ±0.30
 .XX ~~~~ ±0.20
 .XXX ~~~~ ±0.10
 ANGLE ~~~~ ±5°

苏州金维益电子科技有限公司
SUZHOU JINWEIYI ELECTRONICS & TECH CO.,LTD

物料编码 PART NO.	2422XXXXXXMXXX	物料名称 DRAWING	2.54排针 2X1P 双排双立贴无柱 SMT
客户料号 CUSTOMER COPY	20250313003	图号 DWG NO.	202503.13
日期 DATE	2025.03.13	审核 CHECKED	Robert Luo
变更人 CHANGER	Pop Zhong	批准 APPROVED	2025.03.13

A1	210303001	优化版面	21.03.03	Pop Zhong
A0				
版本 REV NO.	变更编号 ECN NO.	描述 DESCRIPTION	变更日期 DATE	变更人 CHANGER

品名规格 PART NO.	物料编码 MATERIAL NO.	图号 DWG NO.	物料名称 DRAWING	图号 DWG NO.	物料名称 DRAWING
	2422XXXXXXMXXX	20250313003	2.54排针 2X1P 双排双立贴无柱 SMT	202503.13	2.54排针 2X1P 双排双立贴无柱 SMT
		20250313003	2.54排针 2X1P 双排双立贴无柱 SMT	202503.13	2.54排针 2X1P 双排双立贴无柱 SMT
		20250313003	2.54排针 2X1P 双排双立贴无柱 SMT	202503.13	2.54排针 2X1P 双排双立贴无柱 SMT

单位 UNITS	比例 SCALE	图幅 SIZE
MM	N:1	A4