



STANDARD	
PA	6.00
W	5.00
D	1.20
H	2.50

TOLERANCES UNLESS OTHERWISE SPECIFIED

.X ~~~~ ±0.30
 .XX ~~~~ ±0.20
 .XXX ~~~~ ±0.10
 ANGLE ~~~~ ±5°

苏州金维益电子科技有限公司
SUZHOU JINWEIYI ELECTRONICS & TECH CO.,LTD

Ordering Informations

2411 XX X N XX M X XXX

① 2411 Pin Header- 2.54 Single Row Series (H2, 5MM)
 ② XX NO. of Contacts Per row 02~20IN 02~10P
 ③ X Insulator Material A=PT C=PA6T D=PA9T F=I²
 ④ N Posts W=With Posts
 ⑤ XX Contact Plated G=Gold Flash G0=08μ" gold G1=1U" Gold G5=10U" Gold S=TiN Plated
 ⑥ M Mounting Type D=DIP R=Right angle M=SMT Z=Recomment U=U Type
 ⑦ X Packing O=PE Bag T=tube A=Tray P=Mylar-Tube R=Reel-CAP M=Var-Reel
 ⑧ XXX Serial NO. 001 001'999

1、SPECIFICATIONS:

Current Rating : 3.0 A
 Contact Resistance : 20mΩ Max
 Insulation Resistance : 1000MΩ Min
 Withstand Voltage : 1000V AC/minute
 Operation Temperature : -40° C ~ +105° C

2、MATERIALS:

Contact Material : Copper Alloy
 Contact Plating : Gold/Tin Plated over Ni
 Insulator Material : PA6T BK (UL94V-0)
 Max Processing Temp : 230° C for 30 Seconds
 260° C for 5~10 Seconds

A1	210303001	优化版面	21.03.03	Pop Zhong
A0				
REV NO.	变更编号 ECN NO.	描述 DESCRIPTION	变更日期 DATE	变更人 CHANGER

客户料号	CUSTOMER COPY
图纸	DRWG
规格	SIZE
1 OF 1	

物料编号	2411XXXXXXMMXX	物料规格	2.54排针-单排 1X2P-单排立贴
图号	20250313003	制图	Pop Zhong
图名		审核	
视图		批准	Robert Luo
投影		批准	
比例		日期	2025.03.13
图幅		图号	
SCALE		比例	N:1
SIZE		图幅	A4