



Recommended PCB Layout  
Layout Tolerance ±0.05mm

1、SPECIFICATIONS:

Current Rating : 2.0 A  
Voltage Rating : 250V AC  
Contact Resistance : 20mΩ Max  
Insulation Resistance : 1000MΩ Min  
Withstand Voltage : 500V AC/minute  
Operation Temperature : -40° C ~ +105° C

2、MATERIALS:

Contact Material : Copper Alloy  
Contact Plating : Gold/Tin Plated over Ni  
Insulator Material : PA6T BK (UL94V-0)  
Max Processing Temp : 260° C for 30~60 Seconds

Ordering Informations

4715 XXX C N XX M R XX

- ①
- ②
- ③
- ④
- ⑤
- ⑥
- ⑦
- ⑧

- ① 4715 BOX Header- 2.0 Series With Window (H5.65MM)
- ② XXX NO. of Contacts 006=6PIN 006~0080P
- ③ C Insulator Material C=PA6T D=PA6T F=ELCP
- ④ N Posts #=Flth Posts N=Without Posts
- ⑤ XX Contact Plated G=Gold Flash G0=0.8U" Gold G1=1U" Gold G5=10U" Gold S=TiN Plated
- ⑥ M Mounting Type D=DIP R=Right Angle M=SMT Z=Recomment
- ⑦ R Packing O=PE Bag T=tube A=Tray P=Mylar-Tube R=Reel-CAP M=Bar-Reel
- ⑧ XX Serial NO. 01 01~99

**苏州金维益电子科技有限公司**  
**SUZHOU JINWEIYI ELECTRONICS & TECH CO.,LTD**

STANDARD	W	6.50
	D	0.00

TOLERANCES UNLESS OTHERWISE SPECIFIED  
X ~~~~ ±0.30  
.XX ~~~~ ±0.20  
XXX ~~~~ ±0.10  
ANGLE ~~~~ ±5°

物料编号	4715XXXXXXMRXX	物料名称	2.0筒牛-01-立轴-带窗
图号	20250313003	图号	2025.03.13
客户料号		图号	2025.03.13
客户料号		图号	2025.03.13

REV NO.	变更编号	变更日期	变更人	变更日期	变更人
ECN NO.	变更编号	变更日期	变更人	变更日期	变更人
1	1	21.03.03	Pop Zhong	21.03.03	Pop Zhong
2	2				
3	3				
4	4				
5	5				
6	6				

REV NO.	变更编号	变更日期	变更人	变更日期	变更人
ECN NO.	变更编号	变更日期	变更人	变更日期	变更人
1	1	21.03.03	Pop Zhong	21.03.03	Pop Zhong
2	2				
3	3				
4	4				
5	5				
6	6				