



With screw nuts

NO. OF PINS	A	B	C	D	E	F	G	H	I	J	K
15P	30.81	25.00	16.34	2.29	1.98	7.90	12.55	5.90	2.54	21.90	8.89
26P	39.14	33.32	24.67	2.29	1.98	7.90	12.55	5.90	2.54	21.90	8.89
44P	53.04	47.04	38.38	2.29	1.98	7.90	12.55	5.90	2.54	21.90	8.89

F	A1	210303001	刷新版面	21.03.03	Pop Zhang
	A0				
	REV. NO.	变更编号	描述	变更日期	变更人
	ECN NO.	变更编号	DESCRIPTION	DATE	CHANGER
	1		2	3	4

TOLERANCES UNLESS OTHERWISE SPECIFIED
 .X ~~~~ ±0.30
 .XX ~~~~ ±0.20
 .XXX ~~~~ ±0.10
 ANGLE ~~~~ ±5°

物料编号		客户料号		页码		1 OF 1	
59F03XXXXXX		XXXXXX		XXXXXX		XXXXXX	
物料规格		图号		图号		图号	
PART NO.		Dwg NO.		Dwg NO.		Dwg NO.	
SUZHOU JINWEIYI ELECTRONICS & TECH CO.,LTD		20250912003		20250912003		20250912003	
D.SUB 母头 三排 MP 冲插 冲针 冲料		DRWING		CHECKED		APPROVED	
Pop Zhang		Reboot Luo		2025.09.12		2025.09.12	
MM		SCALE		N:1		A4	

Ordering Informations

59F03 XX A X XX R X XX

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- 59F03 DB Female Three Row Series
- XX NO. of Contacts 15=15PIN 26=26PIN 44=44PIN
- A Insulator Material A=PT
- X Nuts W=With Nuts H=With Screw Nuts(H5.8)
- XX Contact Plated G=Gold Flash S=6μ" TIN SF=30" Gold/TIN S2=5μ" Gold/TIN S3=10μ" Gold/TIN SW=TIN Plated
- R Mounting Type D=DIP R=Right Angle W=Welding
- X Packing O=PE Bag T=Tube A=Tray
- XX Serial NO. 01'99

1、SPECIFICATIONS:

Current Rating : 3.0 A
 Contact Resistance : 30mΩ Max 500V DC
 Insulation Resistance : 500MΩ Min
 Withstand Voltage : 1000V AC/minute
 Operation Temperature : -40° C ~ +105° C

2、MATERIALS:

Contact Material : Copper Alloy
 Shell Material : Steel NI Plated
 Contact Plating : Contact Area Gold Plated
 Tail Area Tin Plated
 All over NI

Insulator Material : PBT BK (UL94V-0)
 Wave soldering Temp : 260±5° C for 5 Seconds