



1、SPECIFICATIONS:

Current Rating : 3.0 A
 Current Voltage : 250V AC/DC
 Contact Resistance : 20mΩ Max
 Insulation Resistance : 1000MΩ Min
 Withstand Voltage : 1000V AC/minute
 Operation Temperature : -40° C ~ +105° C

2、MATERIALS:

Contact Material : Copper Alloy
 Contact Plating : G/F or Tin over Ni
 Insulator Material : PA6T BK (UL94V-0)
 Max Processing Temp : 260 ± 5° C for 5~10 Seconds

Ordering Informations

58K11 XX X N XX D X XX
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① 58K11 Female Header 2.54 Single Row PC104 Series (Add Insulator)
- ② XX NO. of Contacts Per Row 02=2PIN 02~10P
- ③ X Insulator Material A=PT C=PA6T D=PA6T P=PC
- ④ N Post N=WITHOUT POSTS W=WITH POSTS
- ⑤ XX Contact Plated GF=Gold Flash G=1U" Gold SW=Tin Plated
- ⑥ D Mounting Type D=DIP R=Right Angle M=SMT
- ⑦ X Packing T=Tube A=Tray P=Mylar+Tube
- ⑧ XX Serial NO. 01 01~99

苏州金维益电子科技有限公司
SUZHOU JINWEIYI ELECTRONICS & TECH CO.,LTD

品名规格 PART NO.	2.54X8.5 单排母座_np_DIP_直插_PC104		
物料编码 MATERIAL NO.	58K11XXXXXXDXXX	制图 DRAWING	Pop Zhong 2023.08.08
图号 DWG NO.	20230808001	审核 CHECKED	
视图 PROJECTION		批准 APPROVED	Robert Luo 2023.08.08
客户料号 CUSTOMER COPY		页码 SHEET	1 OF 1

STANDARD	PB	11.00
	PC	3.00

刷新版面 Pop Zhong 21.03.03

A1 210303001

版本 REV NO.	变更编号 ECN NO.	描述 DESCRIPTION	变更日期 DATE	变更人 CHANGER
A0				
1				

单位名称 UNITS	MM
比例 SCALE	N:1
图幅 SIZE	A4