



Recommended PCB Layout
Layout Tolerance ±0.05mm

1、SPECIFICATIONS:

Current Rating : 3.0 A
 Current Voltage : 250V AC/DC
 Contact Resistance : 20mΩ Max
 Insulation Resistance : 1000MΩ Min
 Withstand Voltage : 1000V AC/minute
 Operation Temperature : -40° C ~ +105° C

2、MATERIALS:

Contact Material : Copper Alloy
 Contact Plating : G/F or Tin over Ni
 Insulator Material : PA6T BK (UL94V-0)
 Max Processing Temp : 260±5° C for 5~10 Seconds

Ordering Informations

58K13 XX X N XX D X XX

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① 58K13 Female Header 2.54 Three Row P104 Series (Add Insulator)
- ② XX NO. of Contacts Per Row 03=3PIN 06=6PIN
- ③ X Insulator Material A=PIBT C=PA6T D=PA6T P=PCP
- ④ N Post N=WITHOUT POSTS W=WITH POSTS
- ⑤ XX Contract Plated GF=Gold Flash G=1U" Gold SW=Tin Plated
- ⑥ D Mounting Type D=DIP R=Right Angle M=SMT
- ⑦ X Packing T=Tube A=Tray P=Mylar+Tube
- ⑧ XX Serial NO. 01 01'99

苏州金维益电子科技有限公司
SUZHOU JINWEIYI ELECTRONICS & TECH CO.,LTD

品名规格: 2.54X8.5 三排母座 3XnP DIP 直插 PCI04
 PART NO. MATERIAL NO. 58K13XXXXXXDXDX
 图号: 20230808001
 制图: 2023.08.08
 审核: 2023.08.08
 批准: 2023.08.08
 单位: MM
 比例: N:1
 图幅: A4

A1	210303001	刷新版面	21.03.03	Pop Zhong
A0				
REV NO.	变更编号 ECN NO.	描述 DESCRIPTION	变更日期 DATE	变更人 CHANGER

STANDARD	
PB	16.50
PC	3.00

TOLERANCES UNLESS OTHERWISE SPECIFIED
 .X ~~~~ ±0.30
 .XX ~~~~ ±0.20
 .XXX ~~~~ ±0.10
 ANGLE ~~~~ ±5°

CUSTOMER COPY	客户料号
1 OF 1	页码
PROJECTION	视图

图号	20230808001	制图	2023.08.08	单位	MM
DWG NO.		审核		比例	N:1
		批准		图幅	A4