



1、SPECIFICATIONS:

Current Rating : 3.0 A
 Current Voltage : 250V AC/DC
 Contact Resistance : 20mΩ Max
 Insulation Resistance : 1000MΩ Min
 Withstand Voltage : 1000V AC/minute
 Operation Temperature : -40° C ~ +105° C

2、MATERIALS:

Contact Material : Copper Alloy
 Contact Plating : G/F or Tin over Ni
 Insulator Material : PA6T BK (UL94V-0)
 Max Processing Temp : 260 ± 5° C for 5~10 Seconds

Ordering Informations

58Y11 XX X N XX R X XX
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① 58Y11 Female Header 2.54 Single Row Series (V_Type)
- ② XX NO. of Contacts Per Row 02=2PIN 02~10P
- ③ X Insulator Material A=PT C=PA6T D=PA6T F=LCP
- ④ N Post N=11HOLE POSTS W=11H POSTS
- ⑤ XX Contact Plated GF=Gold Flash G=1U" Gold SW=Tin Plated
- ⑥ R Mounting Type D=DIP R=Right Angle M=SWT
- ⑦ X Packing T=Tube A=Tray P=Mylar+Tube
- ⑧ XX Serial NO. 01 01~99

苏州金维益电子科技有限公司
SUZHOU JINWEIYI ELECTRONICS & TECH CO.,LTD

TOLERANCES UNLESS OTHERWISE SPECIFIED
 .X ~~~~ ±0.30
 .XX ~~~~ ±0.20
 .XXX ~~~~ ±0.10
 ANGLE ~~~~ ±5°

品名规格 PART NO.	58Y11XXXXXXRXX	制图 DRAWING	Pop Zhong	2023.08.08	单位 UNITS	MM
物料号 MATERIAL NO.	58Y11XXXXXXRXX	审核 CHECKED			比例 SCALE	N:1
图号 DWG NO.	20230808001	批准 APPROVED	Robert Luo	2023.08.08	图幅 SIZE	A4

A1	210303001	刷新版面	21.03.03	Pop Zhong	CUSTOMER COPY	页码 SHEET	1 OF 1
A0					客户料号		
版本 REV NO.	变更编号 ECN NO.	描述 DESCRIPTION	变更日期 DATE	变更人 CHANGER			

F	1	2	3	4	5	6
---	---	---	---	---	---	---