



1、SPECIFICATIONS:

Current Rating : 3.0 A
Current Voltage : 250V AC/DC
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstand Voltage : 1000V AC/minute
Operation Temperature : -40° C ~ +105° C

2、MATERIALS:

Contact Material : Copper Alloy
Contact Plating : G/F or Tin over Ni
Insulator Material : PA6T BK (UL94V-0)
Max Processing Temp : 260±5° C for 5~10 Seconds

Ordering Informations

58Y13 XX X N XX R X XX

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① 58Y13 Female Header 2.54 Three Row Series
- ② XX NO. of Contacts Per Row 03=3PIN 03~10P
- ③ X Insulator Material A=PBT C=PA6T D=PA9T P=PCP
- ④ N Post N=WITHOUT POSTS W=WITH POSTS
- ⑤ XX Contact Plated GF=Gold Flash G=1U" Gold SW=Tin Plated
- ⑥ R Mounting Type D=DIP R=Right Angle M=SMT
- ⑦ X Packing T=Tube A=Tray P=Mylar+Tube
- ⑧ XX Serial NO. 01 01~99

TOLERANCES UNLESS OTHERWISE SPECIFIED

X ~~~~ ±0.30
.XX ~~~~ ±0.20
.XXX ~~~~ ±0.10
ANGLE ~~~~ ±5°

苏州金维益电子科技有限公司
SUZHOU JINWEIYI ELECTRONICS & TECH CO.,LTD

2.54X8.5 三排母座 3Xp DIP 弯插

品名规格 PART NO.	物料编码 MATERIAL NO.	制图 DRAWING	审核 CHECKED	批准 APPROVED	客户料号 CUSTOMER COPY	页码 SHEET	1 OF 1	图号 DWG NO.	视图 PROJECTION	比例 SCALE	单位 UNITS	图幅 SIZE
	58Y13XXXXXXRXXX							20230808001		N:1	MM	A4
		2023.08.08			客户料号	页码	1 OF 1					
		2023.08.08			变更日期 DATE	变更人 CHANGER						

A1	210303001	刷新版面	21.03.03	Pop Zhong	变更日期 DATE	变更人 CHANGER						
A0					描述 DESCRIPTION							
版本 REV NO.	变更编号 ECN NO.											

F

E

D

C

B

A

F

E

D

C

B

A

1 2 3 4 5 6