




HIGH	PART NO.
2.00	3022-M
1.50	3122-M
1.00	3222-M



Recommended PCB Layout
Layout Tolerance ±0.05mm



1、SPECIFICATOINS:

Current Rating : 2.0 A
Voltage Rating : 250V AC
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstand Voltage : 500V AC/minute
Operation Temperature : -40° C ~ +105° C

2、MATERIALS:

Contact Material : Copper Alloy
Contact Plating : Gold/Tin Plated over Ni
Insulator Material : PA6T BK (UL94V-0)
Max Processing Temp : 230° C for 30 Seconds
260° C for 5~10 Seconds

Ordering Informations

3022 XX X N XX M X XXX
① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① 3022 Pin Header: 2.0 Dual Row Series (Add Insulator)
- ② XX NO. of Contacts Per row 02=2PIN 02~40P
- ③ X Insulator Material A=PBT C=PA6T D=PA9T F=LC²
- ④ N Posts W=With Posts N=Without Posts
- ⑤ XX Contact Plated GF=Gold Flash G0=0.80" Gold SN=Tin Plated
- ⑥ M Mounting Type D=DIP R=Right Angle M=SMT Z=Recumbent
- ⑦ X Packing 0=PE Bag T=Tube A=Tray R=TAPE&REEL
- ⑧ XXX Serial NO. 001 001~999

STANDARD	
PA	4.00
PB	10.00
W	6.50
D	0.00

TOLERANCES UNLESS OTHERWISE SPECIFIED

.X ~~~~ ±0.30
.XX ~~~~ ±0.20
.XXX ~~~~ ±0.10
ANGLE ~~~~ ±5°

苏州金维益电子科技有限公司
SUZHOU JINWEIYI ELECTRONICS & TECH CO.,LTD

品名规格 PART NO.	2.0排针_双排双塑_2XnP_SMT_立贴				
物料编码 MATERIAL NO.	3022XXNXMXXXX	制图 DRAWING	Pop Zhang	2025.03.13	单位 UNITS MM
图号 DWG NO.	20250313003	审核 CHECKED			比例 SCALE N:1
视图 PROJECTION	第一角	批准 APPROVED	Robert Luo	2025.03.13	图幅 SIZE A4

A1	210303001	优化版面	21.03.03	Pop Zhang					
A0					客户料号				
版本 REV NO.	变更编号 ECN NO.	描述 DESCRIPTION	变更日期 DATE	变更人 CHANGER	CUSTOMER COPY	页码 SHEET	10F1	视图 PROJECTION	