









Recommended PCB Layout
Layout Tolerance±0.05mm

1、SPECIFICATCINS:

Current Rating	:	1.0 A
Current Voltage	:	250V AC/DC
Contact Resistance	:	20mΩ Max
Insulation Resistance	:	500MΩ Min
Withstand Voltage	:	500V AC/minute
Operation Temperature	:	-40° C ~ +105° C

2、MATERIALS:

Contact Material	:	Phosphor Bronze
Shell Material	:	Zinc Alloy Ni Plated
Contact Plating	:	Contact Area 15u″Gold
		Tail Area Tin Plated
		All over Ni 50u″
Insulator Material	:	PBT BK (UL94V-0)
Max Processing Temp	:	265±5° C for 5~10 Seconds

Pins	A	B	C	D	E	F	G	H	I
14P	29.54	23.64	12.58	9.58	7.62	1.27	2.80	17.58	1.905
20P	33.35	27.45	16.39	13.39	11.43	1.27	2.80	21.39	1.905
26P	37.16	31.26	20.20	17.20	15.24	1.27	2.80	25.20	1.905
36P	43.51	37.61	26.55	23.55	21.59	1.27	2.80	31.55	1.905
50P	52.40	46.50	35.44	32.44	30.48	1.27	2.80	40.44	1.905

Ordering Informations

72M11 026 R A XX T 1

- 026: NO. of Contacts — 014=14P, 020=20P, 026=26P, 036=36P, 050=50P
- R: Tail Type — D=DIP, R=Right Angle
- A: Insulaor Material — A=PBT, F=LCP
- XX: Plated — SN=Tin Plated, S4=5U″ Gold, S5=10U″ Gold, S6=15U″ Gold, S7=30U″ Gold
- T: Packing — T=Tube, A=Tray

SZJWY

TOLERANCES UNLESS OTHERWISE SPCIFIED

.X ~~~~ ±0.30
.XX ~~~~ ±0.20
.XXX ~~~~ ±0.10
ANGLE ~~~~ ±5°

苏州金维益电子科技有限公司
SUZHOU JINWEIYI ELECTRONICS &TECH CO;LTD

版本 REV NO.	变更编号 ECN NO.	描述 DESCRIIPTION	变更日期 DATE	变更人 CHANGER
A1	210303001	更新版面	21.03.03	Pop Zhang
A0				

品名规格 PART NO.	SCSI_26P_弯插母座_PC3.4_管装_PBT_锌合金外壳								
物料编码 MATERIAL NO.	72M11026RAXXT1	制图 DRAWING	Pop Zhang	2025.07.15	单位 UNITS	MM
图号 DWG NO.	20250715001	审核 CHECKED			比例 SCALE	N:1
客户料号		页码 SHEET	1 OF 1	视图 PROJECTION		批准 APPROVED	Robort Luo	2025.07.15	图幅 SIZE	A4

CUSTOMER COPY